- 1. (Amended) A serial communication controller for transmitting and receiving a serial data stream including multiple serial data channels having portions which alternate in time with respect to each other, comprising:
 - a plurality of functional units configured to operate in series according to a serial communication protocol, wherein each functional unit is configured to perform a different specific function of said serial communication protocol, and wherein the plurality of functional units operates in time sequence upon the portions of the multiple serial data channels; and

wherein the plurality of functional units is configured to perform said serial communication protocol on the multiple serial data channels.

- 6. (Amended) A serial communication controller for transmitting and receiving a serial data stream including alternating portions of multiple serial data channels, comprising:
 - a plurality of functional units each configured to perform a specific function of a serial communication protocol, wherein each functional unit is a state machine having a set of unique operating states, and wherein each functional unit comprises a programmable state register, and wherein state information stored within the state register of a given functional unit determines the one of the unique operating states in which the functional unit is operating;
 - a memory unit including a separate portion allocated to each of the multiple serial data channels for storing the state information of the functional units; and
 - a microcontroller coupled to each of the plurality of functional units and to the memory unit, wherein the microcontroller is configured to transfer state

0.

information between the plurality of functional units and the memory unit such that the plurality of functional units operates alternately upon the portions of the multiple serial data channels;

- wherein different state information is transferred for each serial data channel depending on which serial data channel's portion is being operated on by the plurality of functional units.
- 11. (Twice Amended) A method for transmitting and receiving a serial data stream including alternating portions of multiple serial data channels, comprising:
 - providing a plurality of functional units each configured to perform a specific function of a serial communication protocol upon the portions of the multiple serial data channels, wherein each functional unit is a state machine having a set of unique operating states, and wherein state information stored within a given functional unit determines the one of the unique operating states in which the functional unit is operating; and
 - transferring state information between the plurality of functional units and a memory unit such that the plurality of functional units operates alternately upon the portions of the multiple serial data channels;
 - wherein different state information is transferred for each serial data channel depending on which serial data channel's portion is being operated on by the plurality of functional units.
 - 14. (Arnended) A serial communication system, comprising:
 - an interface unit adapted for coupling to a transmission medium, wherein the interface unit is configured to receive a receive serial data stream including alternating portions of multiple serial data channels from the

transmission medium and to provide the receive serial data stream;

a timing recovery unit coupled to receive the receive serial data stream from the interface unit, wherein the timing recovery unit is configured to produce a clock signal derived from the receive serial data stream and to provide the receive serial data stream; and

a serial communication controller coupled to receive the clock signal and the receive serial data stream, wherein the serial communication controller comprises a plurality of functional units configured to operate in series according to a serial communication protocol, and wherein each functional unit is configured to perform a different specific function of said serial communication protocol, and wherein the plurality of functional units operates alternately upon the portions of the multiple serial data channels of the receive serial data stream to perform said serial communication protocol on the multiple serial data channels.

REMARKS

Claims 1, 6, 11 and 14 have been amended. Claims 1-16 are pending. Reconsideration is respectfully requested.

Section 103 Rejection:

Claims 1-11 and 14-16 were rejected under 35 U.S.C. § 103(a) as being unpatentable over U.S. Patent No. 5,970,069 to Kumar et al. (hereinafter "Kumar") in view of U.S. Patent No. 5,991,817 to Rowett (hereinafter "Rowett"). Applicants traverse this rejection in light of the following remarks.